

HELI

JS12

**Self Propelled Scissor
Type Aerial Work Platform**



www.heliforklift.net

Manufacturer's Data and Design Characteristics

Manufacture		HELI													
1.1 Model		JS0812	JS0812Li	JS0812E	JS0812ELi	JS1012	JS1012Li	JS1012E	JS1012ELi	JS1212	JS1212Li	JS1212E	JS1212ELi		
Dimension															
2.1 Max.working height	A1	m	10	10	10	10	12	12	12	12	13.9	13.9	13.9	13.9	
2.2 Max.platform height	A2	m	8	8	8	8	10	10	10	10	11.9	11.9	11.9	11.9	
2.3 Overall length	B	m	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	2.4	
2.4 Overall width	C	m	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15	1.15	
2.5 Overall height (guardrail unfolded)	D	m	2.3	2.3	2.3	2.3	2.46	2.46	2.46	2.46	2.60	2.60	2.60	2.60	
2.6 Overall height (guardrail folded)		m	1.71	1.71	1.71	1.71	1.84	1.84	1.84	1.98	1.98	1.98	1.98	1.98	
2.7 Platform size (length x width)	ExF	m	2.25x1.15	2.25x1.15	2.25x1.15	2.25x1.15	2.25x1.15	2.25x1.15	2.25x1.15	2.25x1.15	2.25x1.15	2.25x1.15	2.25x1.15	2.25x1.15	
2.8 Guardrail height	G	m	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	
2.9 Extension size of platform	H	m	1	1	1	1	1	1	1	1	1	1	1	1	
2.10 Ground clearance (retracted state)	I	mm	95	95	95	95	95	95	95	95	95	95	95	95	
2.11 Ground clearance (lifting state)	J	mm	20	20	20	20	20	20	20	20	20	20	20	20	
2.12 Wheelbase	K	m	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	1.85	
Performance															
3.1 Max.number of workers (indoor/outdoor)			2/1	2/1	2/1	2/1	2/1	2/1	2/1	2/1	2/-	2/-	2/-	2/-	
3.2 Rated capacity	kg		450	450	450	450	320	320	320	320	320	320	320	320	
3.3 Rated capacity of extension platform	kg		120	120	120	120	120	120	120	120	120	120	120	120	
3.4 Drive speed (retracted state)	km/h		0~3.2	0~3.2	0~3.2	0~3.2	0~3.2	0~3.2	0~3.2	0~3.2	0~3.2	0~3.2	0~3.2	0~3.2	
3.5 Drive speed (lifting state)	km/h		0~0.8	0~0.8	0~0.8	0~0.8	0~0.8	0~0.8	0~0.8	0~0.8	0~0.8	0~0.8	0~0.8	0~0.8	
3.6 Min.turning radius (inside)	m		0	0	0	0	0	0	0	0	0	0	0	0	
3.7 Min.turning radius (outside)	m		2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	2.2	
3.8 Lifting/Falling time	s		32/35	32/35	32/35	32/35	52/48	52/48	52/48	52/48	52/52	52/52	52/52	52/52	
3.9 Max.work.slop (forward and backward/left and right)	°		3°/1.5°	3°/1.5°	3°/1.5°	3°/1.5°	3°/1.5°	3°/1.5°	3°/1.5°	3°/1.5°	3°/1.5°	3°/1.5°	3°/1.5°	3°/1.5°	
3.10 Max.allowable wind speed (indoor/outdoor)	m/s		0/12.5	0/12.5	0/12.5	0/12.5	0/12.5	0/12.5	0/12.5	0/12.5	0/0	0/0	0/0	0/0	
3.11 Max.allowable lateral force (indoor/outdoor)	N		400/200	400/200	400/200	400/200	400/200	400/200	400/200	400/200	400/0	400/0	400/0	400/0	
3.12 Gradeability	%		30%	30%	30%	30%	25%	25%	30%	30%	25%	25%	30%	30%	
3.13 Control type			Proportional control	Proportional control	Proportional control	Proportional control	Proportional control	Proportional control	Proportional control	Proportional control	Proportional control	Proportional control	Proportional control	Proportional control	
3.14 Drive			Dual front wheels	Dual front wheels	Dual front wheels	Dual front wheels	Dual front wheels	Dual front wheels	Dual front wheels	Dual front wheels	Dual front wheels	Dual front wheels	Dual front wheels	Dual front wheels	
3.15 Brake			Dual rear wheels	Dual rear wheels	Dual rear wheels	Dual rear wheels	Dual rear wheels	Dual rear wheels	Dual rear wheels	Dual rear wheels	Dual rear wheels	Dual rear wheels	Dual rear wheels	Dual rear wheels	
3.16 Tyre size	mm		381x129	381x129	381x129	381x129	381x129	381x129	381x129	381x129	381x129	381x129	381x129	381x129	
Power															
4.1 Lifting/driving motor power	kw		3.3	3.3	3.3/0.7x2	3.3/0.7x2	3.3	3.3	3.3/0.7x2	3.3/0.7x2	4.5	4.5	3.3/0.7x2	3.3/0.7x2	
4.2 Battery voltage/capacity	V/Ah		6×4/180	24/220	6×4/180	24/220	6×4/180	24/220	6×4/180	24/220	6×4/240	24/220	6×4/240	24/220	
4.3 Charger input voltage	VAC		100-240	100-240	100-240	100-240	100-240	100-240	100-240	100-240	100-240	100-240	100-240	100-240	
4.4 Charger output current	A		36	36	36	36	36	36	36	36	36	36	36	36	
4.5 Control voltage	VDC		24	24	24	24	24	24	24	24	24	24	24	24	
Weight															
5.1 Overall weight	kg		2460	2460	2460	2460	2820	2820	2820	2820	2950	2950	2950	2950	

Standard configurations															
Proportional control	Extension platform	Emergency stop device	Intelligent danger alarm	Working timer	Emergency Falling system	Automatic Brake system	Action buzzer	Repair safety arm							
Manual brake release	Automatic Fault diagnosis	Folding guardrail light	Charging action interlock	Auto-protection on holes on the ground	Working strobe Warning light	Oil pipe explosion Proof system	Anti-pinch system	Standard transportati on truck hole							
Optional configurations															
AC power to platform	Platform working light	Platform anti-collision device	Pneumatic pipe to platform	Generator to platform	Intelligent interlock	Folding guardrail	Safety pedal switch	Telematics							



ANHUI HELI CO., LTD.

Add / No.668, FangXing Road, Hefei, China

Fax / +86-551-63639966

Tel / +86-551-63639068(America); 63639258(Europe); 63639358(Asia); 63662105(Africa & Middle East)

* Our products are subject to improvements and changes without notice.



Design/Print: 20230320
Fokell Printing

